

to Claim 17, wherein (P_S) is a polyester (P_S') which is self-dispersible or colloiddally soluble in water.

20. A method for a treatment of textile piece goods from an aqueous liquor Claim 19, wherein (P_S) is employed in the form of an aqueous, concentrated composition (W).

21. A method for a treatment of textile piece goods from an aqueous liquor according to Claim 20, wherein (W) is an aqueous composition which is characterised by a content of (P_S) and

(G) a thickening agent.

22. A method for a treatment of textile piece goods from an aqueous liquor according to Claim 20, wherein (W), in addition to (P_S) and optionally (G), contains at least one of the following components:

(X) a non-ionogenic or anionic emulsifier or a mixture of non-ionogenic and/or anionic emulsifiers,

(Y) an agent for adjusting the pH

and (Z) at least one formulation additive.

23. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to Claim 17, wherein (T) is at least one dye or at least one optical brightener.

24. A method for a treatment of textile piece goods from an aqueous liquor according to Claim 17, in the dyeing or optical brightening of textile material made from polyester fibres, optionally blended with other fibres, in jet dyeing machines.

25. A method for a treatment of textile piece goods from an aqueous liquor according

to Claim 17, in the dyeing or optical brightening of textile material made from polyester microfibrres, optionally blended with other fibres of comparable fineness

26. Wet-acting lubricant for the dyeing or optical brightening of textile piece goods in rope or tubular form from aqueous liquor characterised by a content of (P_S) as defined in Claim 17.
27. Aqueous wet-acting lubricant composition which is an aqueous composition (W) which is defined as in Claim 20.
28. Aqueous wet-acting lubricant composition (W) according to Claim 27, essentially consisting of (P_S) and water and at least one of the additives (G), (X), (Y) and (Z).
29. Process for the production of an aqueous, (G) or/and (X) containing composition (W) according to Claim 28, wherein a melt of (P_S) is mixed in the presence of water with (G) or/and (X) and optionally one or more of (Y) and (Z) is added.
30. Process for the treatment of textile piece goods with a textile treatment agent (T) from aqueous liquor, under conditions which would otherwise in the textile substrate favour the formation of transport folds or the occurrence of friction in or on the substrate, characterised in that the process is carried out in the presence of a water-dispersible or -colloidally soluble, end-capped polyester (P_S), optionally in the form of an aqueous composition (W) as defined in claim 20, as a wet-acting lubricant.

31. Aqueous polyester composition (W'), essentially consisting of (P_S), (G) and water and optionally at least one of the additives (X), (Y) and (Z), in which (P_S) is as defined as a water-dispersible or -colloidally soluble, end-capped polyester, (G) is defined as a thickening agent, and (X), (Y) and (Z) are as defined in Claim 22.

32. Aqueous polyester composition (W'') according to Claim 31, essentially consisting of (P_S'), (G) and water and additionally optionally one or more of the additives (Y) and/or (Z), in the form of an aqueous dispersion or colloidal solution.

10049219.011702